



Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).



NOVITÀ - NEW

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06055		Termostato digitale RANCO 230V 2HP CON 1 Sonda NTC INCLUSA (2 mt) -50° +150° RDTB - 1110 (961) RANCO Digital Temperature Controller 230V 2HP WITH N. 1 NTC PROBE INCLUDED (2 Mt) -50° +150° RDTB - 1110 (961)		 RDTB-1110 Wiring Diagram 	
06058		Termostato digitale RANCO 230V 2HP CON 2 SONDE NTC INCLUSE (2 mt) -50° +150° RDTB - 3210 (974) RANCO Digital Temperature Controller 230V 2HP WITH N. 2 NTC PROBES INCLUDED (2 Mt) -50° +150° RDTB - 3210 (974)		 RDTB-3210 Wiring Diagram 	
NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06523		Controllore Eliwell programmabile a 4 uscite, ID 985 LX 5/8/8/8 A, compatibile Televis System (con Bus Adapter), 3 sonde 12V <i>Eliwell Controller, can be programmed with 4 outputs, ID 985 LX 5/8/8/8 A, compatible Televis System (with Bus Adapter), 3 probes 12V</i>			
06566		Termostato Eliwell ID PLUS 902 - 12V 8A <i>Thermostat Eliwell ID PLUS 902 - 12V 8A</i>		MOD. ELIWELL ID PLUS 	

Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06567		Termostato Eliwell ID PLUS 902 - 230V 8A <i>Thermostat Eliwell ID PLUS 902 - 230V 8A</i>		 MOD. ELIWELL ID PLUS	
06560		Termostato Eliwell ID PLUS 961 - 12V 2HP <i>Thermostat Eliwell ID PLUS 961 - 12V 2HP</i>			
06561		Termostato Eliwell ID PLUS 961 - 230V 2HP <i>Thermostat Eliwell ID PLUS 961 - 230V 2HP</i>			
06562		Termostato Eliwell ID PLUS 971 - 12V 2HP-Buzzer <i>Thermostat Eliwell ID PLUS 971 - 12V 2HP-Buzzer</i>			
06563		Termostato Eliwell ID PLUS 971 - 230V 2HP-Buzzer <i>Thermostat Eliwell ID PLUS 971 - 230V 2HP-Buzzer</i>			
06564		Termostato Eliwell ID PLUS 974 2HP 12V Buzzer <i>Thermostat Eliwell ID PLUS 974 2HP 12V Buzzer</i>			
06565		Termostato Eliwell ID PLUS 974 2HP 230V Buzzer <i>Thermostat Eliwell ID PLUS 974 2HP 230V Buzzer</i>			
06100		Trasformatore 3VA 230/12V <i>3VA 230/12V Transformer</i>			
06516		Controllore Eliwell IS 972 LX sonda PTC o NTC selezionabile a parametro <i>Controller Eliwell IS 972 LX PTC or NTC probe can be selected according to parameter</i>			
06517/S		Modulo Slave Ewem 233 per IS 972 230 V <i>Slave Module Ewem 233 for IS 972 230 V</i>			

Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06528		Controllore IWC 720 230V, 2 relé, 1 sonda NTC, attacco faston, compressore 30A (2 HP), connessioni faston, sonde idonee cod. 06176 o 06178 <i>Controller IWC 720, 230V, 1 relay, probes, Faston fitting, 30A (2 HP) compressor, Faston connections, suitable probes code 06176 or 06178</i>	dima foratura <i>drilling template</i> 150 x 31 profondità <i>depth</i> 45		
06529		Controllore IWC 720 230V, 2 relé, 1 sonda NTC con attacco JST, compressore 30A (2 HP), connessioni Faston, sonde idonee cod. 06188/06189 <i>Controller IWC 720 230V, 1 relay, 1 NTC probes, JST fitting, 30A (2 HP) compressor, Faston connections, suitable probes 06188/06189</i>	dima foratura <i>drilling template</i> 150 x 31 profondità <i>depth</i> 45		
06530		Controllore IWC 720 230V, 2 relé, 2 sonde NTC attacco standard, compressore 30A (2 HP) <i>Controller IWC 720 230V, 2 relays, 2 NTC probes, standard fitting 30A (2 HP) compressor</i>	dima foratura <i>drilling template</i> 150 x 31 profondità <i>depth</i> 60		
06531		Controllore IWC 730 230V, 3 relé, 2 sonde NTC attacco faston, compressore 30A (2 HP), sonde idonee cod. 06176 e 06178 <i>Controller IWC 730 230V, 3 relays, 2 NTC probes, Faston fitting, 30A (2 HP) compressor, suitable probes code 06176 and 06178</i>	dima foratura <i>drilling template</i> 150 x 31 profondità <i>depth</i> 45		
06532		Controllore IWC 730 230V, 3 relé, 2 sonde NTC attacco standard, compressore 30A (2 HP) <i>Controller IWC 730 230V, 3 relays, 2 NTC probes, standard fitting 30A (2 HP) compressor</i>	dima foratura <i>drilling template</i> 150 x 31 profondità <i>depth</i> 60		
06170		Kit morsetti sconnettibili femmina ZZ000072 per IWC 720 (cod.06530) <i>Female disconnectable clamps Kit ZZ000072 for IWC 720 (code 06530)</i>			
06172		Kit morsetti sconnettibili femmina ZZ000073 per IWC 730 (cod.06532) <i>Female disconnectable clamps Kit ZZ000073 for IWC 730 (code 06532)</i>			
06190		Sonda standard PTC in PVC campo -30° +80° C <i>Standard PTC probe in PVC range -30° +80° C colore nero - black colour</i>	6 x 30 L=1500		
06191		Sonda standard NTC in PVC campo -30° +80° C <i>Standard NTC probe in PVC range -30° +80° C colore grigio - grey colour</i>	6 x 40 L=1500		

Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06192		Sonda standard NTC in PVC campo -30° +80° C <i>Standard NTC probe in PVC range -30° +80° C</i> colore grigio – grey colour	6 x 40 L=3000		
06193		Sonda standard PTC in PVC campo -30° +80° C <i>Standard PTC probe in PVC range -30° +80° C</i> colore nero – black colour	6 x 30 L=3000		
06195		Sonda al silicone NTC , campo -50° +110° C <i>Silicone NTC probe, range -50° +110° C</i>	6 x 40 L=1500		
06196		Sonda al silicone PTC, campo -55° +150° C <i>Silicone PTC probe, range -55° +150° C</i>	6 x 40 L=1500		
06197		Sonda al silicone NTC , campo -50° +110° C <i>Silicone NTC probe, range -50° +110° C</i>	6 x 40 L=3000		
06198		Sonda al silicone PTC, campo -55° +150° C <i>Silicone PTC probe, range -55° +150° C</i>	6 x 40 L=3000		
06181		Sonda NTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>NTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP 68 (watertight) black</i>	6 x 40 L=1500		
06180		Sonda PTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>PTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP68 (watertight) black</i>	6 x 40 L=1500		
06183		Sonda NTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>NTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP 68 (watertight) black</i>	6 x 40 L=3000		
06182		Sonda PTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>PTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP68 (watertight) black</i>	6 x 40 L=3000		

Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06184		Sonda NTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>NTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=1500		
06185		Sonda PTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>PTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=1500		
06186		Sonda NTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>NTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=3000		
06187		Sonda PTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>PTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=3000		
06188		Sonda NTC in TPE attacco JST (capsula in plastica) campo -40° +110° C - IP 68, per controllore IWC 720 - 230V con attacco JST <i>NTC probe in TPE 5 x 20 1.5 m JST fitting (plastic capsule) range -40° +110° C - IP 68, for controller IWC 720 - 230V with JST fitting</i>	5 x 20 L=1500		
06189		Sonda NTC in TPE attacco JST (capsula in plastica) campo -40° +110° C - IP 68, per controllore IWC 720 - 230V con attacco JST <i>NTC probe in TPE 5 x 20 1.5 m JST fitting (plastic capsule) range -40° +110° C - IP 68, for controller IWC 720 - 230V with JST fitting</i>	5 x 20 L=3000		
06176		Sonda NTC in PVC, campo -30° +80° C per controllore IWC 720 con attacco Faston <i>NTC probe in PVC, range -30° +80° C for controller IWC 720 - 230V with Faston fitting</i>	6 x 40 L=1500		
06178		Sonda NTC in silicone , campo -50° +110° C per controllore IWC 720 <u>con attacco Faston</u> <i>NTC probe in silicone, range -50° +110° C for controller IWC 720 - 230V with Faston fitting</i>	6 x 40 L=1500		